



Remarks:

Plastic: PBT +25% GF (UL 94V-0)
 Terminal: phosphor bronze C5191 R-H Nickel
 15u "Min. Plated bright tin 30u""50u" Min.


Performance:

Rated current: 1A, AC / DC
 Rated voltage: 200V
 Contact resistance: 30mΩ Max.
 Insulation resistance: 1000MΩ MIN.
 Withstand voltage: 500V RMS
 Operating Temperature: -55 °C to +85 °C.



PIN	A	B	PIN	A	B
2	10.74	2.54	15	43.76	35.56
3	13.28	5.08	16	46.30	38.10
4	15.82	7.62	17	48.84	40.64
5	18.36	10.16	18	51.38	43.18
6	20.90	12.70	19	53.92	45.72
7	23.44	15.24	20	56.46	48.26
8	25.98	17.78	21	59.00	50.80
9	28.52	20.32	22	61.54	53.34
10	31.06	22.86	23	64.08	55.88
11	33.60	25.40	24	66.62	58.42
12	36.14	27.94	25	69.16	60.96
13	38.68	30.48	26	71.70	63.50
14	41.22	33.02	27	74.24	66.04

適用FFC/FPC
 APPLICABLE FFC/FPC



PCB LAYOUT

UNITS mm					
MAT'L					
FINISH	PART NO.(INTENDED USE) 2.54-A-nPW	TITLE: 2.54MM 90° 薄膜插座			
Q'TY PCS	APPD:	DWG NO.: 2.54-A-nPW			
	CHKD:		SCALE	SHEET	REV.
	DR: HU 2016.09.28		1/1	1/1	A

X.± 0.3	X° ± 5°
.X± 0.25	.X° ± 2°
.XX± 0.20	.XX° ± 1°
.XXX± 0.10	.XXX° ± 0.5°