

WAFER CONNECTOR DIP RIGHT ANGLE

2000 SERIES - 2.00MM







Specifications

- Applicable wire: AWG 28-22
- Rated Voltage: 250V AC/DC
- Rated current: 3A
- Withstand Voltage: 800V AC/min
- Operation temperature: -25°C to +85°C
- Insulation resistance: 1000MΩ min
- Contact resistance: 10mΩ max

Material

- Insulator: Nylon 66 UL94-V2
- Contact material: Brass
- Contact plating: Sn300" Over Ni30-50u"


Poles	DIM.A	DIM.B
2x2P	2.0	5.9
2x3P	4.0	7.9
2x4P	6.0	9.9
2x5P	8.0	11.9
2x6P	10.0	13.9
2x7P	12.0	15.9
2x8P	14.0	17.9
2x9P	16.0	19.9
2x10P	18.0	21.9
2x11P	20.0	23.9
2x12P	22.0	25.9
2x13P	24.0	27.9
2x14P	26.0	29.9
2x15P	28.0	31.9
2x16P	30.0	33.9
2x17P	32.0	35.9
2x18P	34.0	37.9
2x19P	36.0	39.9
2x20P	38.0	41.9



2x4P~2x20P

2x3P

2x2P



P.C.B LAYOUT



Ordering Information

2000DR2 - (XX) X X 02

1. Connector Series
2. Number of pins per row
3. Contact plating
 - A = Gold Flash
 - B = Tin
4. Color
 - W = White

				OPERATION		DRAW	BEN	12.04.18	SCALE	FIT	votre partenaire en électronique	
				X.X	±0.30							
				X.XX	±0.20	APPROVE			SIZE	A4	PART NO.	2000DR2 - XXXX 02
				X.XXX	±0.10							
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	DIM	TOL							



PART NO. 2000DR2 - XXXX 02
TITLE: 2 Wafer Npin