



CELLION SAS

3	SHELL	1	SPCC/BRASS	NI PLATED
2	CONTI	4	COPPER ALLOY	G/F AU/TIN PLATED
1	HOUSING	1	(PBT)THERMOPLASTIC	QUL 94V-0) BLACK/WHITE
No.	PART NAME	QTY	MATERIAL	REMARK

DESCRIPTION USB2.0 A/T FEMALE 180 度DIP 带鱼叉脚 H=10.0

DRAWING NO B150325--003 PART NO BUSF04W1N1209

THIRD ANGLE PROJECTION	REVISION	A	UNIT	MM	DRAWN	ROGERLAN
LINEAR	±0.50	X	ANGLE	±5°	CHECKED	
XX	±0.38	XX	SCALE	N/A	APPROVED	
XXX	±0.25	XXX	SHEET	1/1		

Specification
 Electrical Characteristics:
 Contact Current Rating:1 Amperes.
 Dielectric Withstanding Voltage:AC 500V R.M.S.
 Insulation Resistance:500MΩ Min.
 Contact Resistance:30mΩ Max.
 Mechanical Characteristics:
 Mating Force:3.57kg Max.
 Umating Force:0.7kg Min.
 Material:
 Housing:PBT
 Contact:BRASS C2680 Plating Au1u
 Shell:SPCC/BRASS.Plating Ni over all