



RECOMMENDED PCB LAYOUT  
GENERAL TOLERANCES: ±0.05

- NOTES:  
1. ELECTRONIC:  
CONTACT RESISTANCE: 30mohm MAX  
INSULATION RESISTANCE: 1000 Mohm MIN  
WITHSTAND VOLTAGE: AC 500V, 1min.  
2. MECHANICAL:  
DURABILITY: 1500 CYCLE.  
3. ENVIRONMENT CHARACTERISTICS:  
OPERATING TEMPERATURE: -55°C TO +105°C

3	SHELL	1	STEEL T=0.3mm	NI PLATED
2	CONTACT	4	COPPER ALLOY T=0.2mm	AU/TIN PLATED
1	HOUSING	1	(LCP) THERMOPLASTIC	(UL 94V-0) BLACK
No.	PART NAME	QTY	MATERIAL	REMARK

### CELLION SAS

DESCRIPTION: USB 2.0 AF 板上全贴 H7.0 带定位柱

DRAWING NO: BT171025-001 PART NO.: BUSFO4B2N1176

THIRD ANGLE PROJECTION	REVISION	A	UNIT	MM	DRAWN	DAVIDWU
	LINEAR	ANGLE	SCALE	N/A	CHECKED	
	X. ±0.50 X. ±5°	X.X ±0.38 X.X ±2'	SHEET	1/1	APPROVED	