



MATERIAL
 INSULATOR: PBT 30% G.F.; COLOR: WHITE/BLACK; UL94V-0
 CONTACT: BRASS; GOLD FLASH PLATED ON CONTACT
 AREA AND TIN PLATED ON SOLDER AREA
SHELL: SPCC/BRASS
ENVIRONMENTAL
 OPERATING TEMPERATURE: $-25^{\circ}\sim+85^{\circ}\text{C}$.
ELECTRICAL:
 CONTACT CURRENT RATING: 1 Amp.
 DIELECTRIC WITHSTANDING: AC 1000V min./PER MINUTE.
 INSULATING RESISTANCE: 500M Ω min./AC 500V DC
 CONTACT RESISTANCE: 30m Ω Max

| No. | PART NAME | QTY | MATERIAL | REMARK |
|-----|-----------|-----|---------------------|------------------------|
| 3 | SHELL | 1 | SPCC/BRASS | NI PLATED |
| 2 | 4PIN | 4 | COPPER ALLOY | G/F AU/TIN PLATED |
| 1 | HOUSING | 1 | (PBT) THERMOPLASTIC | (UL 94V-0) WHITE/BLACK |

CELION SAS

| | | | | |
|-------------|-----------------------------|----------|---------------|--|
| DESCRIPTION | USB2.0 A/T FEMALE 侧插DIP 90度 | | | |
| DRAWING NO | BT140525016 | PART NO. | BUSF04**NI26* | |

| THIRD ANGLE PROJECTION | REVISION | | UNIT | DRAWN | CHECKED | APPROVED |
|------------------------|-----------------|----------------------|------|----------|---------|----------|
| | LINEAR | ANGLE | MM | | | |
| | X. ± 0.50 | X. $\pm 5^{\circ}$ | N/A | ROGERLAN | | |
| | X.X ± 0.38 | X.X $\pm 2^{\circ}$ | | | | |
| | X.XX ± 0.25 | X.XX $\pm 1^{\circ}$ | | | | |

1 2 3 4 5

A B C D