



PCB LAYOUT

MATERIAL: PBT 30% G.F.; COLOR: WHITE; UL94V-0  
 INSULATOR: PBT 30% G.F.; COLOR: WHITE; UL94V-0  
 CONTACT: BRASS; GOLD FLASH PLATED ON CONTACT AREA AND TIN PLATED ON SOLDER AREA  
 SHELL: BRASS/SPCC  
 ENVIRONMENTAL  
 OPERATING TEMPERATURE: -25~+85°C.  
 ELECTRICAL:  
 CONTACT CURRENT RATING: 1 Amp.  
 DIELECTRIC WITHSTANDING: AC 1000V min. PER MINUTE.  
 INSULATING RESISTANCE: 500MΩ min. AC 500V DC  
 CONTACT RESISTANCE: 30mΩ Max

3	SHELL	1	SPCC	NI PLATED
2	4PIN	4	COPPER ALLOY	G/F AU/TIN PLATED
1	HOUSING	1	(PBT) THERMOPLASTIC	(UL 94V-0) WHITE
No.	PART NAME	QTY	MATERIAL	REMARK

### CELION SAS

DESCRIPTION: USB2.0 B/T FEMALE 180度 DIP

DRAWING NO: BT140525009 PART NO: BUSF04W2N1254

THIRD ANGLE PROJECTION	REVISION	A	UNIT	MM	DRAWN	ROGERLAN
	LINEAR X	±0.50	ANGLE X	±5°	SCALE	N/A
		XX	±0.38	XX	±2°	SHEET
		XX	±0.25	XX	±1°	APPROVED

