



RECOMMEND P.C.B.LAYOUT

- NOTES:
- ELECTRONIC:
    - CONTACT RESISTANCE: 30mohm MAX
    - INSULATION RESISTANCE: 100 Mohm MIN
    - WITHSTAND VOLTAGE:AC 100V,1min.
  - MECHANICAL:
    - INSERTION FORCE:3.5KG MAX.
    - WITHDRAWAL FORCE:0.8KG MIN.
    - DURABILITY: 10000 CYCLE.
  - ENVIRONMENT CHARACTERISTICS:
    - OPERTING TEMPERATURE: -25°C TO +85°C

3	SHELL	1	STAINLESS T=0.3	TIN PLATED
2	PIN	5	COPPER ALLOY T=0.15	AU PLATED
1	HOUSING	1	HIGH THERMOPLASTIC	BLACK UL 94V-0
No.	PART NAME	QTY	MATERIAL	REMARK

### CELION SAS

DESCRIPTION		MICRO USB5P FEMALE B TYPE SMT 无内柱			
DRAWING NO	BT150912-003	PART NO.	BUSF05B1T11150		
THIRD ANGLE PROJECTION	REVISION	ANGLE	UNIT	DRAWN	ROGERLAN
	X. XX XXX	±0.50 ±0.38 ±0.25	MM	CHECKED	
		±5° ±2° ±1°	N/A	APPROVED	
			1/1		