


No.	PART NAME	QTY	MATERIAL	REMARK
5	SHELL	1	SUSS304	NI PLATED
4	SPIN	5	COPPER ALLOY	G/F AU/TIN PLATED
3	4PIN	4	PHOSPHOR BRONZE	G/F AU/TIN PLATED
2	COVER	1	THERMOPLASTIC (PBT)	(UL94V-0) BLUE(300C)
1	HOUSING	1	THERMOPLASTIC (PBT)	(UL94V-0) BLUE(300C)

CELION SAS

DESCRIPTION 四层 USB3.0 A/T FEMALE 90度DIP 无弹片蓝胶芯

DRAWING NO BT161007-001 PART NO. BUSF36L3M1205

THIRD ANGLE PROJECTION	REVISION	ANGLE	UNIT	DRAWN	CHECKED
X, ±0.50	X, ±0.38	X, ±5°	MM	DAVIDWU	
XXX ±0.25	XXX ±1°				



LINEAR SCALE N/A
SHEET 1/1
APPROVED

NOTES:
1.ELECTRONIC:
CONTACT RESISTANCE: 30mohm MAX
INSULATION RESISTANCE: 1000 Mohm MIN
WITHSTAND VOLTAGE:AC 500V,1min.

2.MECHANICAL:
DURABILITY: 1500 CYCLE.

3.ENVIRONMENT CHARACTERISTICS:
OPERATING TEMPERATURE:-55°C TD +105°C

4.RECOMMANDER PCB THICKNESS 1.2 TD 1.60MM

1

2

3

4

5