



变更标记	日期	变更内容	签名	核准		
P 0(XXX)	No. of Contact	A ±0.25	B ±0.13	C ±0.25	D ±0.38	E ±0.25
009	9	16.92	24.99	33.98	39.58	33.98
015	15	25.25	33.32	42.30	47.90	42.30
025	25	38.96	47.04	56.02	61.62	55.92
037	37	55.42	63.50	72.48	78.08	72.48

**MATERIALS AND FINISH**

SHELL : STEEL,TIN FINISHED  
 INSULATOR : PBT UL94V-0 BLACK COLOR  
 SIGNAL CONTACT: COPPER ALLOY,GOLD PLATED  
 WATERTIGHT FRAME: PBT UL94-0 BLACK COLOR  
 O-RING : SILICONE  
 EPOXY SEALANT: EPOXY

**ELECTRICAL CHARACTERISTICS**

SIGNAL CONTACT CURRENT RATING 5.0 AMPS  
 SIGNAL CONTACT RESISTANCE 10mΩ MAX  
 DIELECTRIC WITHSTANDING VOLTAGE: 1000 V AC MIN.  
 INSULATION RESISTANCE : 5GΩ MIN.  
 TEMPERATURE RATING : -55°C ~ +105°C  
 DEGREE OF PROTECTION: IP67 ACCORD

**CELION SAS**

未注公差		设计		刘峰		品名规格		DB 公置焊板式 防水连接器 带防水圈	
X.	±0.30	审核		料号	DBM1800830	型号			
XX	±0.20	核准		日期	2010-07-21	图号			
XXX	±0.10	单位	mm	比例	1:1	版次	A/1		
XXXX	±0.05								
X° ±2° XX° ±1°									